







AIR

PRODUCT MATERIAL Die-cast Aluminium LIGHT SOURCE Osram Oslon

MODULE LIFETIME Approx. 30.000 hours Fixture excluding driver, **SELECT OPTION** DRIVER

○ 3 = RAL 9003 white COLORS (Δ) 5 = RAL 9005 black


BEAM ANGLE ADJUSTABLE Yes - 0-60° - 360° SIZE 50 X 55mm






OPTIONS

OPTIONAL BEAM ANGLE Art. no.: 4925.999.38.9 ANTI-GLARE RING Black anti-glare ring Gold anti-glare ring Art. no.: 4925.030.00.9 700mA 1.4-2.8W On/off OPTION DRIVERS Art. no.: 0103.700.10.1 Phase cut 700mA 1-20W Art. no.: 0120.700.20.0 700mA 1-20W 1/10V Art. no.: 0120.700.30.1 700mA 1-20W Art. no.: 0120.700.40.0 DALI Europlug 2000mm 2 X 0,75 **OPTION POWER CABLE** Art. no.: 0502.075.20.0 Connected to driver/fixture Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0 Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0





Anti-glare ring

AIR

INFORMATION

WARRANTY 3 Years

Full warranty only applies when fixture is purchased in combination with recommended driver.



Due to the small hole size, the drivers can only be placed externally

LiteTime International reserves the right to modify or change technical, contruction or LED specifications due to continuous improvements of our products and lightsources. The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.

ART.NR.	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOUR TEMPERATURE	CRI	TC LIFETIME	mA
Δ see colors									
4925.700.21.Δ	Oslon	Osram	174lm	2,1W	83lm/W	2700K	>90	30.000 Hrs	700mA