



CAP R1

PRODUCT MATERIAL	Die-cast Aluminium
LIGHT SOURCE	Bridgelux
MODULE LIFETIME	Approx. 35.000 hours
DRIVER	Fixture excluding driver, SELECT OPTION
COLORS (Δ)	☐ 3 = RAL 9003 white ☒ 5 = RAL 9005 black
BEAM ANGLE	28°
ADJUSTABLE	Yes
SIZE	105 X 77mm



OPTIONS

GLASS COVER CLEAR	Glass IP44 Art. no.: 0053.999.99.0
OPTION DRIVERS	On/off 350mA 6-10W Art. no.: 0110.350.10.3
	Phase cut 350mA 5-10W Art. no.: 0110.350.30.1
	1/10V 350mA 5-10W Art. no.: 0110.350.30.1
	DALI 350mA 3-18W Art. no.: 00118.350.40.0
OPTION POWER CABLE Connected to driver/fixture	Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0
	Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0
	Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0



INFORMATION

WARRANTY	3 Years
-----------------	---------

Full warranty only applies when fixture is purchased in combination with recommended driver.

LiteTime International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources. The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.

CAP R1



ART.NR.	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOUR TEMPERATURE	CRI	TC LIFETIME	mA
Δ see colors									
4005.990.28.Δ	BXRA	Bridgelux	600lm	6,6W	86lm/W	2700K	>80	35.000 Hrs	350 mA