



BASIC 13

PRODUCT MATERIAL

Die-cast aluminium

LIGHT SOURCE

MR16 / GU10 LED / LMR50

MODULE LIFETIME

Approx. 30.000 hours

DRIVER

See options

COLORS (Δ)

○ 3 = RAL 9003 white

● 5 = RAL 9005 black

BEAM ANGLE



ADJUSTABLE

Yes

SIZE

130 X 130 X 43mm **or incl. LMR50 X 100mm**



OPTIONS LMR50

GLASS COVER CLEAR	Glass IP44 art. no.: 0053.999.99.0	€ 7,50
DIMMABLE DRIVERS 350mA <i>IN COMBINATION WITH THIS LUMINAIRE. ADDITIONAL PRICE.</i>	Fixed output 350mA 10W art. no.: 0000.000.00.0	€ 0,00
	Phase-cut Dimmable 350mA 10W art. no.: 0110.350.10.1	€ 29,50
	1/10v Dimmable 350mA 10W art. no.: 0110.350.10.1	€ 29,50
	DALI Dimmable 350mA 18W art. no.: 0118.350.15.1	€ 55,00

BASIC 13



INFORMATION

! Only luminaire body, lightsource and/or driver excluded

All drivers include a cable and plug

Including an assemble plate to mount a single unit into a double, triple, quadruple or "L" shape unit easily in a short time

LiteTime International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and lightsources.



ART.NR.	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOUR TEMPERATURE	CRI	TC LIFETIME	BEAM ANGLE	mA	SALES PRICE
Δ see colors											
4908.001.98.Δ	MR16	~	~	Max. 50W	~	~	~	~	~	~	
4908.002.98.Δ	GU10	~	~	Max. 50W	~	~	~	~	~	~	
4908.171.20.Δ	LMR50	Bridgelux V6	575lm	6,8W	85lm/W	2700K	>90	30.000 Hrs	20°	350	
4908.172.30.Δ	LMR50	Bridgelux V6	575lm	6,8W	85lm/W	2700K	>90	30.000 Hrs	30°	350	
4908.173.20.Δ	LMR50	Bridgelux V6	600lm	6,8W	88lm/W	3000K	>90	30.000 Hrs	20°	350	
4908.174.30.Δ	LMR50	Bridgelux V6	600lm	6,8W	88lm/W	3000K	>90	30.000 Hrs	30°	350	
4908.175.20.Δ	LMR50	Sharp GW6	563lm	6,6W	85lm/W	2000 - 2800K DTW	>80	30.000 Hrs	20°	350	
4908.176.30.Δ	LMR50	Sharp GW6	563lm	6,6W	85lm/W	2000 - 2800K DTW	>80	30.000 Hrs	30°	350	