


Colours	■ ■ ■
Housing	Aluminium, die cast
Fixture type	Track light
Module	Philips Fortimo SLM Led module
Driver	Driver incorporated in track adapter
Light Output module	1100lm, 2000lm, 3000lm, 4500lm
CCT	2700K, 3000K, 3500K, 4000K, 5700K
CRI	>80Ra, >90Ra
Beam angles	15°, 24°, 45°, 60°
Adapter	Powergear® 3-phase Ultimate adapter included
Rotatable	355°
Tiltable	90°
LED modules	Standard, Premium ,Food, DTW
Dimming Options	Triac, DALI, 1-10V, Casambi
Options	Honeycomb, Glass
Expected Lifetime	50.000h (L80/B10)
Photobiological safety	RG1 unlimited
Power factor	> 0.9
LOR	> 90%
Colour consistency	3 SDCM
Warranty	5 years warranty on LED module and driver



Net Weight	Dimensions carton L x W x H	Qty outer carton
grams	00 x 00 x 00 cm	

Available LED Modules

Description	Lumen	Watt	Lm/W	CCT	CRI						
Philips Fortimo SLM G7	1100lm	6W	183	827,830,840	>80	Philips Fortimo SLM G7	3000lm	20W	150	940PW	>90
Philips Fortimo SLM G7	1100lm	8W	138	927,930,930PW	>90	Philips Fortimo SLM G7	3000lm	31W	96	922 PA (2200K)	>90
Philips Fortimo SLM G7	1100lm	7W	157	940PW	>90	Philips Fortimo SLM G7	3000lm	24W	125	930 PC	>90
Philips Fortimo SLM G7	1100lm	10W	110	922 PA (2200K)	>90	Philips Fortimo SLM G7	4500lm	27W	166	827, 830, 840	>80
Philips Fortimo SLM G7	1100lm	8W	137	930 PC	>90	Philips Fortimo SLM G7	4500lm	33W	136	927, 930, 930PW	>90
Food Warm White	1100lm	11W	100	925 FWW	>90	Philips Fortimo SLM G7	4500lm	30W	150	940PW	>90
Meat Premium Red	1100lm	16W	69	920 MPR	>90						
Fresh Fish	1100lm	13W	85	940 FF	>90						
Philips Fortimo SLM G7	2000lm	12W	167	827, 830, 840	>80						
Philips Fortimo SLM G7	2000lm	15W	133	927, 930, 930PW	>90						
Philips Fortimo SLM G7	2000lm	14W	143	940 PW	>90						
Philips Fortimo SLM G7	2000lm	19W	105	922 PA (2200K)	>90						
Philips Fortimo SLM G7	2000lm	16W	125	930 PC	>90						
Food Warm White	2000lm	22W	91	925 FWW	>90						
Meat Premium Red	2000lm	30W	67	920 MPR	>90						
Fresh Fish	2000lm	22W	91	940 FF	>90						
Philips Fortimo SLM G7	3000lm	18W	166	827, 830, 840	>80						
Philips Fortimo SLM G7	3000lm	22W	136	927, 930, 930PW	>90						



LED modules
Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K
Premium White (PW): for fresh white and depth of colour in retail environments
*) Lumen output of LED module (COB)
) Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.
The power of the complete fixture will be slightly higher due to the power consumption of the driver.
) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.
Technical data can be changed by Internova without prior notice.