



PRODUCT MATERIAL	Die-cast aluminium
LIGHT SOURCE	Bridgelux DtW
DRIVER	Including phase cut dimmable driver
COLORS (Δ)	○ 3 = RAL 9003 white ● 5 = RAL 9005 black
BEAM ANGLE	24°
ADJUSTABLE	Rotating 350°, 55° tiltable
DIMMABLE	Yes
SIZE	292 X 62mm



VENUS DUO

OPTIONS


OPTIONAL BEAM ANGLE	<p>36° Art. no.: 2 X 3066.010.36.0</p> <p>50° Art. no.: 2 X 3066.010.50.0</p>
ANTI-GLARE RING	<p>Black anti-glare ring</p> <p>Gold mat anti-glare ring Art. no.: 2 X 3066.030.00.9</p>
HONEYCOMB	Art. no.: 2 X 3066.040.00.0
OPTION DRIVERS	<p>1/10V</p> <p>DALI 500mA 12-20W Art. no.: 0120.500.40.2</p>

INFORMATION

WARRANTY	3 Years
-----------------	---------

Also available in track and recessed version

LiteTime reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and lightsources. The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.



Anti-glare ring



Honeycomb

ART.NR.	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOUR TEMPERATURE	CRI	TC LIFETIME	mA
5068.135.24.Δ	DtW	Bridgelux	2 X 900lm	2 X 10W	90lm/W	1800-3000K	DTW >90	50,000 Hrs	500mA

Δ see colors