


| | |
|------------------------|---|
| Colours | <div> <div></div> <div></div> </div> |
| Housing | Aluminium, die cast |
| Fixture type | Surface mounted |
| Module | Standard Dim-to-Warm LED module |
| Driver | Standard TRIAC dimmable driver |
| Light Output module | 900lm |
| CCT | 1800K – 3000K |
| CRI | >90Ra |
| Beam angles | 40° |
| Rotatable | 0° |
| Tilttable | 0° |
| LED modules | Dim-To-Warm LED module |
| Dimming Options | TRIAC (standard) |
| Options | N/A |
| Expected Lifetime | 30.000h (L70/B30) |
| Photobiological safety | RG1 unlimited |
| Power factor | > 0.9 |
| Colour consistency | 3 SDCM |
| Warranty | 3 years warranty on LED module and driver |



| Net Weight | Dimensions carton L x W x H | Qty outer carton |
|------------|-----------------------------|------------------|
| 595 grams | 13 x 15 x 13 | 20 |

Available LED Modules

| Description | Lumen | Watt | Lm/W | CCT | CRI |
|-------------|-------|------|------|---------------|-----|
| Dim-to-Warm | 900lm | 7W | 74 | 1800K – 3000K | >90 |



LED modules:

¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³⁾ Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.