



LOOK TOO

PRODUCT MATERIAL

Die-cast aluminium

LIGHT SOURCE

Bridgelux V8 array

MODULE LIFETIME

Approx. 35.000 hours

DRIVER

Fixture excluding driver, select option

COLORS (Δ)

● 5 = RAL 9005 black
○ + ● 35 = RAL 9003 white + RAL 9005 black

BEAM ANGLE



ADJUSTABLE

350° rotational

90° rotational spot head

SIZE

212 X 100 X 103mm



OPTIONS

OPTION DRIVERS	Fixed output 500mA 12W art. no.: 0112.500.10.0
	Phase-cut dimmable 500mA 10W art. no.: 0110.500.20.2
	1/10V dimmable On request
	DALI dimmable 500mA 6-10W art. no.: 0110.500.40.0


LOOK TOO

INFORMATION

WARRANTY

2 Years

LiteTime International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and lightsources. Full warranty only applies when fixture is purchased in combination with recommended driver.



ART.NR.	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOUR TEMPERATURE	CRI	TC LIFETIME	mA
Δ see colors									
6002.179.33.Δ	V8 Array	Bridgelux	2 X 970lm	2 X 9,3W	113lm/W	2700K	>90	35.000 Hrs	500mA