

## TRACK /SURFACE



**Colours**  
**Housing**  
**Fixture type**  
**Module**  
**Driver**  
**Light Output module**

**CCT**  
**CRI**  
**Beam angles**

**Adapter**  
**LED modules**  
**Dimming Options**  
**Expected Lifetime**  
**Photobiological safety**  
**Power factor**  
**LOR**  
**Colour consistency**  
**Warranty**




Powder coated steel  
Track light  
Osram V-S LED Linear  
Osram V-S comfortline  
1140mm: 4500lm, 6000lm  
1700mm: 6000lm, 9000lm  
3000K, 4000K, 5000K, 6500K  
>80Ra, >90Ra  
30°, 60°, 90°, 110°, Retail Symmetric,  
Retail A-Symmetric  
Powergear® 3-phase adapter included  
Standard  
DALI, Casambi  
>50.000h (L90/B50)  
RG1 unlimited  
> 0.9  
> 90%  
3 SDCM  
5 years warranty on LED module and driver

Net Weight	Dimensions carton L x W x H	Qty outer carton
1665 grams	116 x 8 x 7	6
2415 grams	172 x 8 x 7	6


## Available LED Modules

Description	Lumen	Watt	Lm/W	CCT	CRI
Vossloh-Schwabe Linear LED	4500lm	25W	181	830	
Vossloh-Schwabe Linear LED	4500lm	23W	196	840, 850, 865	
Vossloh-Schwabe Linear LED	4500lm	31W	145	930	
Vossloh-Schwabe Linear LED	4500lm	27W	164	940, 950	
Vossloh-Schwabe Linear LED	6000lm	33W	181	830	
Vossloh-Schwabe Linear LED	6000lm	31W	196	840, 850, 865	
Vossloh-Schwabe Linear LED	6000lm	41W	145	930	
Vossloh-Schwabe Linear LED	6000lm	37W	164	940, 950	
Vossloh-Schwabe Linear LED	9000lm	50W	181	830	
Vossloh-Schwabe Linear LED	9000lm	46W	196	840, 850, 865	
Vossloh-Schwabe Linear LED	9000lm	62W	145	930	
Vossloh-Schwabe Linear LED	9000lm	55W	164	940, 850	


## LED Inside




Narrow 30°




Medium 60°




Wide 90°



Extra wide 110°



Retail Symmetric



Retail A-Symmetric

### LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

<sup>1)</sup> Lumen output of LED module (COB)

<sup>2)</sup> Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

<sup>3)</sup> Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.