



PRODUCT MATERIAL	Die-cast aluminium
ADAPTER	48V adapter
LIGHT SOURCE	Bridgelux V8
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Including Dali driver
COLORS (Δ)	☐ 3 = RAL 9003 white ☒ 5 = RAL 9005 black
BEAM ANGLE	☒ 30° ☐ 20°
ADJUSTABLE	Yes
SIZE	Ø90 X 30mm




OPTIONS

WIRELESS DIMMABLE	Zigbee or Casambi
--------------------------	-------------------

INFORMATION

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.



ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA	DEGREE
Δ See colors										
5825.270.20.Δ	V8	Bridgelux	650lm	10W	65lm/W	2700K	>90	50.000 Hrs	350mA	20°
5825.270.30.Δ	V8	Bridgelux	650lm	10W	65lm/W	2700K	>90	50.000 Hrs	350mA	30°