



PRODUCT MATERIAL	Die-cast aluminium
ADAPTER	48V adapter
LIGHT SOURCE	Bridgelux BXKC
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Including Dali driver
COLORS (Δ)	☐ 3 = RAL 9003 white ☒ 5 = RAL 9005 black
BEAM ANGLE	24°
ADJUSTABLE	Yes
SIZE	Ø59 X 73mm




OPTIONS

OPTIONAL BEAM ANGLE	15° Art. no.: 5819.020.15.0
	36° Art. no.: 5819.020.36.0
ANTI-GLARE RING	Black anti-glare ring Included
	Gold anti-glare ring Art. no.: 3066.030.00.9
HONEYCOMB	Art. no.: 3066.040.00.0
WIRELESS DIMMABLE	Zigbee or Casambi

INFORMATION

Keylight International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.



ANTI-GLARE RING



HONEYCOMB



ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
Δ See colors									
5819.270.24.Δ	BXKC	Bridgelux	750lm	10W	75lm/W	2700K	>90	50.000 Hrs	500mA
5819.300.24.Δ	BXKC	Bridgelux	750lm	10W	75lm/W	3000K	>90	50.000 Hrs	500mA