



INTERIOR RECESSED CIRCULAR

PRODUCT MATERIAL

Die-cast Aluminium

LIGHT SOURCE

Cree LED module

MODULE LIFETIME

Approx. 35.000 hours

DRIVER

Fixture including on/off driver

COLORS (Δ)

○ 3 = RAL 9003 white

● 5 = RAL 9005 black

BEAM ANGLE



ADJUSTABLE

No

SIZE

30 X 24mm

OPTIONS

OPTION DRIVERS	Phase cut 250mA 1-11W Art. no.: 0111.250.20.0
	1/10V 250mA 1-14W Art. no.: 0114.250.30.0
	DALI 250mA 1-10W Art. no.: 0110.250.40.0
OPTION POWER CABLE Connected to driver/fixture	Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0
	Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0
	Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0

INFORMATION

WARRANTY


3 years




Due to the small hole size, the drivers can only be placed externally



Mello



Hole size



Technical drawing

ART.NR.	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOUR TEMPERATURE	CRI	TC LIFETIME	mA
Δ see colors									
4310.002.30.Δ	LED module	Cree	65lm	2W	32lm/W	2700K	>90	35.000 Hrs	250mA