



Housing Aluminium

**RAL colour** 9004 (Black), 9003 (White), 1036 (Gold)

Fixture type Pendant lighting Module Pridgelux V10

**Driver** TRIAC dimmable driver incorporated in ceiling cap

Lumen output1100lmCCT2700K, 3000KCRI>90RaBeam angles15°, 24°, 40°Expected Lifetime50.000h L80/B10Photobiological safetyRG1 unlimited

Power factor > 0.9 UGR < 19 Colour consistency 3 SDCM

Warranty 3 years warranty on LED module and driver

Also available with SkyTrack® 3-phase track adapter



## **LED MODULES**

## **OPTIONS**

## **ANTI-GLARE RINGS**













## **LED MODULE OPTIONS**

Description	Lumen	Watt	Lm/W	сст	CRI	Description	Lumen	Watt	Lm/W	сст	CRI
Bridgelux V10	1100Lm	15W	73	927, 930	>90Ra						

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 3500K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

1) Lumen output of LED module (COB)

<sup>2)</sup> Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.
The power of the complete fixture will be slightly higher due to the power consumption of the driver

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

3) Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.