



Colour



Led track fixture. Created to meet the lighting requirements of commercial areas, sales areas, commercial galleries, common areas. It is compact and easy to assemble, flexible; right and left side can be powered by two different phases as illustrated below.



TRACK	3,4 Kg	DRIVER INCLUDED	220-240V 50/60 Hz	IP 20	CE	IECEE CE SCHEME
-------	--------	-----------------	----------------------	-------	----	--------------------

TECHNICAL FEATURES

BODY

Sheet steel and aluminium die-cast joint

COOLING

Passive heat dissipation

POWER

2X28 W Led - 2X33 W System

2X33 W Led - 2X39 W System - HO Version

The data relating to wattages is provided as a guideline and is subject to change

OPTICAL SYSTEM

PMMA lens

LIFE TIME (TA = 25°C)

maintenance: L80B10 ≥ 55.000 h

COLOUR RENDERING

CRI>80 (3000 K - 4000 K)

CODE	LENS	LED TECHNICAL DATA	COLOUR	ACCESSORIES
BMO	30 30°			
	60 60°	HE0W 2X28 W 9250 lm 3000 K	B WHITE	
	11 110°	HE0C 2X28 W 9700 lm 4000 K	N BLACK	0
	AL Asymmetrical left	HO0W 2X33 W 10800 lm 3000 K	G GREY	
	AR Asymmetrical right	HO0C 2X33 W 11300 lm 4000 K		
	BW Batwing			

Coding example

BMO30HE0WB0

BMO CODE + 30 LENS + HE0W LED TECHNICAL DATA + B COLOUR + 0 ACCESSORIES

AVAILABLE ON REQUEST



DALI 3500K

CASAMBI
SOLO / ONLY 2X28W

