

PRODUCT MATERIAL	Die-cast aluminium
LIGHT SOURCE	Bridgelux
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Excluding driver, SELECT OPTION
COLORS (Δ)	<input type="radio"/> 3 = RAL 9003 white <input checked="" type="radio"/> 5 = RAL 9005 black
BEAM ANGLE	15°
ADJUSTABLE	No
SIZE	Ø20 X 56mm



OPTIONS



DRIVER OPTIONS 48V	On/off	48V 500mA 1-18W Art. no.: 0118.500.80.0
	DALI	48V 500mA 1-20W Art. no.: 0120.500.90.0
DRIVER OPTIONS 500mA	On/off	500mA 1-6W Art. no.: 0106.500.10.2
	Phase cut	500mA 2-10W Art. no.: 0110.500.20.9
	DALI	500mA 1-10W Art. no.: 0110.500.40.3
POWER CABLE OPTIONS Connected to driver/fixture		Europug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0
		Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0
		Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0

INFORMATION

Always select a driver option and add the selected driver to your order.

Full warranty only applies when fixture is purchased in combination with recommended driver.

Due to the small hole size, the drivers can only be placed externally.



ARTICLE NUMBER	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	VOLT	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
4281.500.15.Δ	Bridgelux	35lm	2W	18lm/W	3V	2700K	>90	35.000 Hrs	500mA