



PRODUCT MATERIAL	Die-cast aluminium
LIGHT SOURCE	Bridgelux V8 Array
MODULE LIFETIME	Approx. 50.000 hours
DRIVER	Excluding driver, SELECT OPTION
COLORS	☐ 3 = RAL 9003 white ☒ 5 = RAL 9005 black
BEAM ANGLE	 33°
ADJUSTABLE	No
SIZE	83 X 83 X 74mm



OPTIONS

DRIVER OPTIONS 350mA	On/off	350mA 6-10W Art. no.: 0110.350.10.3
	Phase cut	350mA 1-7W Art. no.: 0107.350.20.2
	DALI	350mA 3-18W Art. no.: 0118.350.40.0 Max. 2 fixtures connected in serie per driver
DRIVER OPTIONS 500mA	On/off	500mA 6-10W Art. no.: 0110.500.10.0
	Phase cut	500mA 6-10W Art. no.: 0110.500.20.7
	DALI	500mA 4-18W Art. no.: 0118.500.40.0
POWER CABLE OPTIONS Connected to driver/fixture		Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0
		Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0
		Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0



INFORMATION

Always select a driver option and add the selected driver to your order.

 Full warranty only applies when fixture is purchased in combination with recommended driver.

INSERTS




White



White / black



Black



Black / gold

ARTICLE NUMBER	COLOR	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
5107.996.35.3	☐ white	V8 Array	Bridgelux	565lm	6,2W	91lm/W	2700K	>90	35.000 Hrs	350mA
5107.996.35.35	☐ ☒ white / black	V8 Array	Bridgelux	565lm	6,2W	91lm/W	2700K	>90	35.000 Hrs	350mA
5107.996.35.5	☒ black	V8 Array	Bridgelux	565lm	6,2W	91lm/W	2700K	>90	35.000 Hrs	350mA
5107.996.35.59	☒ ☐ black / gold	V8 Array	Bridgelux	565lm	6,2W	91lm/W	2700K	>90	35.000 Hrs	350mA
5109.996.50.3	☐ white	V8 Array	Bridgelux	760lm	9,2W	82lm/W	2700K	>90	35.000 Hrs	500mA
5109.996.50.35	☐ ☒ white / black	V8 Array	Bridgelux	760lm	9,2W	82lm/W	2700K	>90	35.000 Hrs	500mA
5109.996.50.5	☒ black	V8 Array	Bridgelux	760lm	9,2W	82lm/W	2700K	>90	35.000 Hrs	500mA
5109.996.50.59	☒ ☐ black / gold	V8 Array	Bridgelux	760lm	9,2W	82lm/W	2700K	>90	35.000 Hrs	500mA