





<b>PRODUCT MATERIAL</b>	Die-cast aluminium
<b>LIGHT SOURCE</b>	Citizen CLU701
<b>MODULE LIFETIME</b>	Approx. 35.000 hours
<b>DRIVER</b>	Excluding driver, <b>SELECT OPTION</b>
<b>COLORS (Δ)</b>	<input type="radio"/> <b>3</b> = RAL 9003 white <input checked="" type="radio"/> <b>5</b> = RAL 9005 black
<b>BEAM ANGLE</b>	 <b>30°</b>
<b>ADJUSTABLE</b>	No
<b>SIZE</b>	Ø64 X 95mm




## OPTIONS

<b>OPTIONAL BEAM ANGLE</b>	 <b>38°</b> Art. no.: 4941.010.38.0
<b>DRIVER OPTIONS</b>	<b>On/off</b> 250mA 7-13W Art. no.: 0115.250.10.0 Size: 100 x 43 x 22,5mm
	<b>Phase cut</b> 250mA 7-10W Art. no.: 0110.250.20.4 Size: 100 x 50 x 19mm
	<b>1/10V</b> 260mA 1-14W Art. no.: 0114.250.30.0 Size: 111 x 52 x 22mm This driver can only be placed externally
	<b>DALI</b> 250mA 6-13W Art. no.: 0114.250.40.1 Size: 97,2 x 43 x 30mm
<b>POWER CABLE OPTIONS</b> Connected to driver/fixture	Europlug 2000mm 2 X 0,75 Art. no.: 0502.075.20.0
	Wieland GST 18/3 male 2000mm 3 X 0,75 Art. no.: 0501.183.20.0
	Wieland T connector GST 18/3 200mm 3 X 0,75 Art. no.: 0500.183.20.0



## INFORMATION

Always select a driver option and add the selected driver to your order.

 Full warranty only applies when fixture is purchased in combination with recommended driver.

ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
Δ See colors									
4981.250.30.Δ	CLU701	Citizen	770lm	7,5W	102lm/W	2700K	>90	35.000 Hrs	250mA
4981.300.30.Δ	CLU701	Citizen	828lm	7,5W	110lm/W	3000K	>90	35.000 Hrs	250mA

LiteTime reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.