

PRODUCT MATERIAL	Steel and aluminium
LIGHT SOURCE	Philips LED module
MODULE LIFETIME	Approx. 30.000 hours
DRIVER	Including on/off driver
COLORS (Δ)	○ 3 = RAL 9003 white ● 5 = RAL 9005 black ● 6 = RAL 9006 alu
SIZE	305 X 66mm





OPTIONS

COLORS	Available in all RAL colours on request Additional price + 10%
DIMMABLE	Dali dimmable
EMERGENCY	3 hours
MOVEMENT SENSOR	On request
DAYLIGHT CONTROL SENSOR	On request
TUNABLE WHITE	On request
CYAN ENHANCED STATIC	On request
WIRELESS DIMMABLE	Masterconnect, Easy Air/Zigbee

INFORMATION

Nominal lifetime L80/B10 @70.000 h / 25°C

- ⚠ **Bespoke size & product features available**
- ⚠ The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.



ARTICLE NUMBER	OPTICS	GROSS LUMEN OUTPUT	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI
Δ See colors						
55.00240.83.E.50.LNS.Δ	50°	1100lm	7W	157m/W	3000K	>80
55.00240.81.E.50.LNS.Δ	50°	1100lm	7W	157m/W	3500K	>80
55.00240.84.E.50.LNS.Δ	50°	1100lm	7W	157m/W	4000K	>80
55.00241.83.E.50.LNS.Δ	50°	1900lm	12W	158lm/W	3000K	>80
55.00241.81.E.50.LNS.Δ	50°	1900lm	12W	158lm/W	3500K	>80
55.00241.84.E.50.LNS.Δ	50°	1900lm	12W	158lm/W	4000K	>80
55.00240.83.E.80.LNS.Δ	80°	1100lm	7W	157m/W	3000K	>80
55.00240.81.E.80.LNS.Δ	80°	1100lm	7W	157m/W	3500K	>80
55.00240.84.E.80.LNS.Δ	80°	1100lm	7W	157m/W	4000K	>80
55.00241.83.E.80.LNS.Δ	80°	1900lm	12W	158lm/W	3000K	>80
55.00241.81.E.80.LNS.Δ	80°	1900lm	12W	158lm/W	3500K	>80
55.00241.84.E.80.LNS.Δ	80°	1900lm	12W	158lm/W	4000K	>80
55.00240.83.E.ASY.LNS.Δ	Asymetrisch	1100lm	7W	157m/W	3000K	>80
55.00240.81.E.ASY.LNS.Δ	Asymetrisch	1100lm	7W	157m/W	3500K	>80
55.00240.84.E.ASY.LNS.Δ	Asymetrisch	1100lm	7W	157m/W	4000K	>80
55.00241.83.E.ASY.LNS.Δ	Asymetrisch	1900lm	12W	158lm/W	3000K	>80
55.00241.81.E.ASY.LNS.Δ	Asymetrisch	1900lm	12W	158lm/W	3500K	>80
55.00241.84.E.ASY.LNS.Δ	Asymetrisch	1900lm	12W	158lm/W	4000K	>80