



VENUS T MINI

PRODUCT MATERIAL

Die-cast aluminium

ADAPTER

3-phase track adapter

LIGHT SOURCE

Bridgelux DtW

DRIVER

Including phase cut dimmable driver

COLORS (Δ)

○ 3 = RAL 9003 white

● 5 = RAL 9005 black

BEAM ANGLE



ADJUSTABLE

Rotating 350°, 90° tiltable

DIMMABLE

Yes

SIZE

73 X 59mm

OPTIONS

OPTIONAL BEAM ANGLE



Art. no.: 3066.010.36.0



Art. no.: 3066.010.50.0

ANTI-GLARE RING

Black anti-glare ring

Gold mat anti-glare ring

Art. no.: 3066.030.00.9

HONEYCOMB

Art. no.: 3066.040.00.0

INFORMATION

WARRANTY


5 Years

Also available in surface and recessed version

LiTeTime reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources. The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.



VENUS T MINI



Technical drawing



Anti-glare ring



Honeycomb

ART.NR.	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOUR TEMPERATURE	CRI	TC LIFETIME	mA
Δ see colors									
3066.125.24.Δ	DtW	Bridgelux	900lm	10W	90lm/W	1800-3000K DTW	>90	50,000 Hrs	250mA