

Colours	□ ■
Housing	Aluminium, die cast
Fixture type	Track light
Module	Philips Fortimo SLM LED module
Driver	Driver incorporated in track adapter
Light Output module	1100lm, 2000lm*
CCT	2700K, 3000K, 4000K, 5700K*
CRI	>80Ra, >90Ra
Beam angles	15°, 24°, 40°
Adapter	Powergear® 3-phase Ultimate adapter included
Rotatable	350°
Tiltable	90°
LED modules	Standard
Dimming Options	DALI, Casambi
Filter Options	N/A
Expected Lifetime	50.000h (L80/B10)
Photobiological safety	RG1 unlimited
Power factor	> 0.9.
Colour consistency	3 SDCM
Warranty	5 years warranty on LED module and driver




Net Weight	Dimensions carton L x W x H	Qty outer carton
465 grams	8 x 7 x 20 cm	1

\* Other specific lumen output or CCT possible upon request

## Available LED Modules

Description	Lumen	Watt	Lm/W	CCT	CRI
Philips Fortimo SLM G7	1100lm	6W	183	827,830,840	>80
Philips Fortimo SLM G7	1100lm	8W	138	927,930,930PW	>90
Philips Fortimo SLM G7	1100lm	7W	157	940PW	>90
Philips Fortimo SLM G7	2000lm	12W	167	827, 830, 840	>80
Philips Fortimo SLM G7	2000lm	15W	133	927, 930, 930PW	>90
Philips Fortimo SLM G7	2000lm	14W	143	940 PW	>90



LED modules  
Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K  
Premium White (PW): for fresh white and depth of colour in retail environments

<sup>1)</sup> Lumen output of LED module (COB)

<sup>2)</sup> Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

<sup>3)</sup> Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.