



PINO CLICK 1

PRODUCT MATERIAL

Die-cast aluminium

LIGHT SOURCE

Bridgelux V8 array

MODULE LIFETIME

Approx. 35.000 hours

DRIVER

Including Phase cut dimmable driver

COLORS (Δ)

○ 3 = RAL 9003 white

● 5 = RAL 9005 black

BEAM ANGLE



ADJUSTABLE

Yes - 0-60° - 360°

SIZE

See technical drawing

OPTIONS

OPTIONAL BEAM ANGLE			€ 5,00
	Art. no.: 4912.010.36.0		
ANTI-GLARE RING	Black anti-glare ring	Included	
	White anti-glare ring	€ 9,50	
	Art. no.: 4912.922.99.3		
GLASS	Gold anti-glare ring	€ 9,50	
	Art. no.: 4912.922.99.9		
	Prismatic	€ 7,50	
	Art. no.: 4912.933.94.0		
	Frosted	€ 7,50	
HONEYCOMB	Art. no.: 4912.933.90.0		
	Striped	€ 7,50	
	Art. no.: 4912.933.96.0		
OPTION DRIVERS	Art. no.: 4912.933.91.0	€ 7,50	
	Art. no.: 4912.933.91.0	€ 7,50	
OPTION DRIVERS	1/10V	500mA 7-10W Art. no.: 0110.500.30.2	€ 40,00
	DALI	500mA 6-10W Art. no.: 0110.500.40.2	€ 50,00

INFORMATION

WARRANTY


3 Years

Also available in 2 light square canopy and 3 light round canopy version

LiTeTime International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and lightsources.



PINO CLICK 1



Technical drawing



Anti-glare ring



Striped

Frosted

Prismatic



Honeycomb

ART.NR.	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOUR TEMPERATURE	CRI	TC LIFETIME	mA	SALES PRICE
Δ see colors										Incl. driver
5032.001.23.Δ	V8 array	Bridgelux	845lm	9,2W	91lm/W	2700K	>90	35.000 Hrs	500mA	€ 120,00