



## PINO CLICK 2

### PRODUCT MATERIAL

Die-cast aluminium

### LIGHT SOURCE

Bridgelux V8 array

### MODULE LIFETIME

Approx. 35.000 hours

### DRIVER

Including Phase cut dimmable driver

### COLORS (Δ)

○ 3 = RAL 9003 white

● 5 = RAL 9005 black

### BEAM ANGLE



### ADJUSTABLE

Yes - 0-60° - 360°

### SIZE

See technical drawing

### OPTIONS

#### OPTIONAL BEAM ANGLE



Art. no.: 4912.010.36.0

#### ANTI-GLARE RING

Black anti-glare ring

White anti-glare ring

Art. no.: 2 X 4912.922.99.3

Gold anti-glare ring

Art. no.: 2 X 4912.922.99.9

#### GLASS

Transparent

Art. no.: 2 X 4912.933.99.0

Prismatic

Art. no.: 2 X 4912.933.94.0

Frosted

Art. no.: 2 X 4912.933.90.0

Striped

Art. no.: 2 X 4912.933.96.0

#### HONEYCOMB

Art. no.: 2 X 4912.933.91.0

#### OPTION DRIVERS

**1/10V** 500mA 20W  
Art. no.: 0137.110.50.0

**DALI** 500mA 6-20W  
Art. no.: 0120.500.40.0

### INFORMATION

#### WARRANTY


3 Years

Also available in 1 and 3 light round canopy version

LiteTime International reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and lightsources. The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.



PINO CLICK 2



Technical drawing



Anti-glare ring



Striped

Frosted

Prismatic



Honeycomb

| ART.NR.       | LAMP TYPE | BRAND     | LUMINOUS FLUX | OUTPUT POWER | MODULE EFFICIENCY | COLOUR TEMPERATURE | CRI | TC LIFETIME | mA    |
|---------------|-----------|-----------|---------------|--------------|-------------------|--------------------|-----|-------------|-------|
| Δ see colors  |           |           |               |              |                   |                    |     |             |       |
| 5032.002.23.Δ | V8 array  | Bridgelux | 2 X 740lm     | 2 X 9W       | 82lm/W            | 2700K              | >90 | 35.000 Hrs  | 500mA |