


Colours	☐ ■
Housing	Aluminium
Fixture type	Surface mounted
Module	Citizen LED's
Driver	OSRAM (TRIAC dimmable)
Light Output module	1500lm
CCT	2700K
CRI	>90Ra
Beam angles	50° (gold inner ring or black inner ring)
Inner Ring	Gold – black housing, Black – white housing
LED modules	Standard
Dimming Options	TRIAC (standard), DALI
Options	N/A
Expected Lifetime	40.000h (L70/B30)
Power factor	> 0.9
UGR	< 19
Colour consistency	3 SDCM
Warranty	3 years warranty on LED module and driver



Net Weight	Dimensions carton L x W x H	Qty outer carton
860 grams	15 x 15 x 15 cm	14

## Available LED Modules

Description	Lumen	Watt	Lm/W	CCT	CRI
Citizen LED	1500lm	20W	75	927	>90

LED modules:

<sup>1)</sup> Lumen output of LED module (COB)

<sup>2)</sup> Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

<sup>3)</sup> Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.

