

η_{ef} (lm/W)
86-118

ART C-TRU

Body:



Grey (RAL 9006) painted aluminium frame, metal ceiling gear box
See page 77 for other available colors

Optic:


Translucent acrylic layer + microprismatic or opal cover

Installation:

Pendant assembly, suspension set included



ART Dekor A



ART Dekor B



Versions of fittings:

		polar	direct	indirect	control
ART	Only direct light		100%	0%	ON/OFF DALI
ART.... DI18	1 channel wiring, direct light 80% / indirect light 20%		80%	20%	ON/OFF DALI
ART.... DI15	1 channel wiring, direct light 50% / indirect light 50%		50%	50%	ON/OFF DALI
ART.... DI2	2 channels wiring, direct light 0 - 50% / indirect light 0 - 50%		0% - 50%	0% - 50%	ON/OFF DALI BT
ART.... RGB	white direct + RGBW indirect		0% - 50%	0% - 50%	BT RGB
ART.... MIXW	2 channels wiring, direct light 0 - 50% / indirect light 0 - 50%, tunable white		0% - 50%	0% - 50%	DALI TW BT TW
ARTSRS	PHILIPS EASY AIR system included		0% - 50%	0% - 50%	EASY AIR

Codes: ART5000DI18M3GPNA/DALI

ART	5000	DI18	M	3	G	P	N	A	/DALI
Luminaire type pendant	Light output	control: DI18 – 1CH control, 80% direct DI15 – 1CH control, 50% direct DI2 – 2CH control RGB – RGB indirect MIXW - tunable white	body length: M = rectangle 1210x200 mm	Color temperature 3 = 3000K, 4 = 4000K, 5 = 5700K	Frame color W = white B = black G = grey	Driver box assembly: P = surface V = recessed	Cover N – prizma O – opal	Decor:	Driver type: ND – no dimmable DALI – dimmable DALI

THE MANUFACTURER CONTINUES TO DEVELOP PRODUCTS THROUGHOUT THEIR LIFETIME. THEREFORE, THE COMPANY RESERVES THE RIGHT TO MODIFY MATERIALS, COMPONENTS, AND TECHNICAL PARAMETERS WITHOUT NOTICE. LUMINOUS OUTPUT AND ELECTRICAL LOAD HAVE AN INITIAL TOLERANCE OF +/- 10 % FROM NOMINAL. FAILURE OF ONE LED LIGHT POINT WITHIN A LUMINAIRE DOES NOT IMPAIR FUNCTIONAL PERFORMANCE AND SO IS NOT CLASSIFIED AS REASON FOR COMPLAINT.

EK	P(W)	Lumen	A (mm)	B (mm)	C1 (mm)	C2 (mm)	X (mm)	Y (mm)	R (mm)	R1 (mm)	Kg	Price (€)
ART5000DI1M4GPNA/ND	45	5300	1 210	200	22	37	440	45	1 030	440	5,0	330,93
ART5000DI1M4GPNA/DALI											389,14	
ART5000DI2M4GPNA/DALI											5,2	505,92
ART5000DI18MMIXWGPNA											5,0	525,32
ART5000DI18MMIXWGPNA/BTC												731,35
ART5000DI2M3(4)RGB/WPN/BTC												5,2

