

**PREMIUM LED PANEL**

**Body:**

White painted (RAL 9003) aluminium frame

**Optic:**

Transluce acrylic desk

KO – opal cover

KN – microprismatic cover

**Version (body shape)**

FIT..A 600 (625) – square 600x600 mm (625x625)

FIT..B 600 – rectangle 600x300 mm

FIT..C 600 – rectangle 1200x300 mm

**Installation way:**

FIT – recessed installation into modular ceiling 600 or 625 mm. Using accessories the panel can be also installed as surface or recessed into a gypsum plasterboard.

FITP – surface or recessed installation into modular ceiling 600 or 625 mm. Using accessories the panel can be also UNI 2 installed as pendant or recessed into a gypsum plasterboard

**Accessories:**

UQRAM – white painted aluminium frame for surface installation

ZH/UNI2 – universal 2-wires suspension

QVESTRAM – white painted aluminium frame for recessed installation into a gypsum plasterboard

51009913 – magnetic holder for surface installation on a gypsum plasterboard

VESTRAMA600 – white painted metal frame for recessed installation of QN or QPN into gypsum plasterboard ceiling

NM – independent emergency module

VESTSET – set of clips for recessed installation of QN or QPN into modular ceiling with hidden profiles


$\eta_{ef}$  (lm/W)  
109-140




2200	2700	3000	4000	5700	6500	MIX	RGB	
✗	○	○	●	○	○	○	✗	✗
●	○	○	○	○	○	○	○	○

● default      ○ optional      ✗ not possible







FIT KN



FIT KO



FIT



FITP

FIT	W	lm		modul 600		modul 625		kg
		KO	KN	A	B	A	B	
FIT3000A	24	3 000	3 100	596	596	622	622	5,0
FIT4000A	35	4 400	4 500					
FIT5000A	49	5 500	5 700					
FIT6000A	57	6 300	6 600					
FIT2000B	16	1 950	2 000	596	296	622	310	2,8
FIT4000B	35	3 800	4 000					
FIT4000C	35	4 100	4 200					
FIT6000C	57	6 200	6 400	1196	296	1245	310	5,0
FIT3000A / 90	24	x	2 650	596	596	622	622	
FIT4000A / 90	35	x	3 950					
FIT5000A / 90	49	x	5 000					
FIT6000A / 90	57	x	5 650					

FIT EFFI	W	lm		modul 600		modul 625		kg
		KO	KN	A	B	A	B	
FIT3500A	27	3 700	3 800	596	596	622	622	5,0
FIT4500A	35	4 800	4 900					

FITP	W	lm		modul 600		modul 625		X/R	Y/S	kg
		KO	KN	A	B	A	B			
FITP3000A	24	3 000	3 100	596	596	622	622	170	170	5,3
FITP4000A	35	4 400	4 500							
FITP5000A	49	5 500	5 700							
FITP6000A	57	6 300	6 600							
FITP4000C	35	4 100	4 200	1196	296	1245	310	410	90	
FITP6000C	57	6 200	6 400							

lm - luminaire light output



Codes: FIT4000A3KN600/ND

FIT	4000	A	3	KN	600	/ND
Luminaire type FIT - recessed / pendant fitting FITP recessed / surface / pendant fitting*						
Light output						
Body shape A - square - 600x600 mm B - rectangle - 600x300 mm C - rectangle - 300x1200 mm						
Color temperature 3 = 3000K, 4 = 4000K, 5 = 5700K						
Cover type: KN - microprizma KO - opal						
Modul 600 625						
Driver type: ND - no dimmable DALI - dimmable DALI						

