

Louvre luminaire with sensor



**EVAL, 1x LED, 1200mm, microALDP
+ opal profile , surfaced/suspended,
3000-4000K, 700mA DALI, BT control**



Luminaire properties

Product category:	Ceiling / wall luminaires	Effective luminous flux (lm):	2250
System power (W):	18	Luminaire efficacy (lm/W):	85
Rated lifetime L80/B50 (h):	50000	Degree of protection (IP):	IP20
Color housing:	White	Suitable for suspended mounting:	Yes
Material housing:	Steel		
Light source included:	Yes		
Suitable for surface mounting:	Yes	Suitable for ceiling mounting:	Yes
Made in Czech republic:	Yes		

Light source

Light source type:	LED	Color temperature (K):	3000-4000
Color rendering index CRI:	80-89	Replaceability:	Removeable light source, replaceable ballast
Light source type:	1991200183001	Energy efficiency class:	C

Optical system

Optical system:	KV	Light outlet:	Direct
Type of grid:	High-gloss	Light sharing:	Symmetric
Material cover:	Plastic, opal	Radiation angle:	Wide beam 41-80°

Dimensions

Length (mm):	1223	Width (mm):	98
Height/depth (mm):	50	Built-in length (mm):	960
Built-in width (mm):	52	Size version:	M
Weight (kg):	2,4		

Electrical values

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
Dimming manufacturer's proprietary system:	Yes		