

|                         |                                                                                   |
|-------------------------|-----------------------------------------------------------------------------------|
| <b>PRODUCT MATERIAL</b> | Steel and aluminium                                                               |
| <b>LIGHT SOURCE</b>     | Philips LED Module                                                                |
| <b>MODULE LIFETIME</b>  | Approx. 30.000 hours                                                              |
| <b>DRIVER</b>           | Including on/of driver                                                            |
| <b>COLORS (Δ)</b>       | <p>○ 3 = RAL 9003 white</p> <p>● 5 = RAL 9005 black</p> <p>● 6 = RAL 9006 alu</p> |
| <b>BEAM ANGLE</b>       | <p>▲ 30° ▲ 55° ▲ 65°</p>                                                          |
| <b>ADJUSTABLE</b>       | No                                                                                |
| <b>SIZE</b>             | Ø90 X 200mm                                                                       |




## OPTIONS

|                                |                                                                   |
|--------------------------------|-------------------------------------------------------------------|
| <b>COLORS</b>                  | Available in all RAL colours on request<br>Additional price + 10% |
| <b>DIMMABLE</b>                | Dali dimmable                                                     |
| <b>SUSPENSION SET</b>          | 1500mm suspension set on request                                  |
| <b>COLOUR RENDERING INDEX</b>  | >80 in standard, other on request                                 |
| <b>MOVEMENT SENSOR</b>         | On request                                                        |
| <b>DAYLIGHT CONTROL SENSOR</b> | On request                                                        |
| <b>TUNABLE WHITE</b>           | On request                                                        |
| <b>CYAN ENHANCED STATIC</b>    | On request                                                        |
| <b>WIRELESS DIMMABLE</b>       | Masterconnect, Easy Air/Zigbee                                    |

## INFORMATION

Nominal lifetime L80/B10 @70.000 h / 25°C

- ! Bespoke size & product features available
- ! The light source in this product can be replaced with an equivalent module made by Philips, Osram or Tridonic.



| ARTICLE NUMBER          | LENGTH | GROSS LUMEN OUTPUT | OUTPUT POWER | MODULE EFFICIENCY | COLOR TEMPERATURE | CRI |
|-------------------------|--------|--------------------|--------------|-------------------|-------------------|-----|
| <b>1127MM</b>           |        |                    |              |                   |                   |     |
| Δ See colors            |        |                    |              |                   |                   |     |
| 55.01605.83.E.30.LNS. Δ | 30°    | 4400lm             | 26W          | 169lm/W           | 3000K             | >80 |
| 55.01605.81.E.30.LNS. Δ | 30°    | 4400lm             | 26W          | 169lm/W           | 3500K             | >80 |
| 55.01605.84.E.30.LNS. Δ | 30°    | 4400lm             | 26W          | 169lm/W           | 4000K             | >80 |
| 55.01605.83.E.55.LNS. Δ | 55°    | 4400lm             | 26W          | 169lm/W           | 3000K             | >80 |
| 55.01605.81.E.55.LNS. Δ | 55°    | 4400lm             | 26W          | 169lm/W           | 3500K             | >80 |
| 55.01605.84.E.55.LNS. Δ | 55°    | 4400lm             | 26W          | 169lm/W           | 4000K             | >80 |
| 55.01605.83.E.65.LNS. Δ | 65°    | 4400lm             | 26W          | 169lm/W           | 3000K             | >80 |
| 55.01605.81.E.65.LNS. Δ | 65°    | 4400lm             | 26W          | 169lm/W           | 3500K             | >80 |
| 55.01605.84.E.65.LNS. Δ | 65°    | 4400lm             | 26W          | 169lm/W           | 4000K             | >80 |
| <b>1407MM</b>           |        |                    |              |                   |                   |     |
| 55.01606.83.E.30.LNS. Δ | 30°    | 5500lm             | 33W          | 166lm/W           | 3000K             | >80 |
| 55.01606.81.E.30.LNS. Δ | 30°    | 5500lm             | 33W          | 166lm/W           | 3500K             | >80 |
| 55.01606.84.E.30.LNS. Δ | 30°    | 5500lm             | 33W          | 166lm/W           | 4000K             | >80 |
| 55.01606.83.E.55.LNS. Δ | 55°    | 5500lm             | 33W          | 166lm/W           | 3000K             | >80 |
| 55.01606.81.E.55.LNS. Δ | 55°    | 5500lm             | 33W          | 166lm/W           | 3500K             | >80 |
| 55.01606.84.E.55.LNS. Δ | 55°    | 5500lm             | 33W          | 166lm/W           | 4000K             | >80 |
| 55.01606.83.E.65.LNS. Δ | 65°    | 5500lm             | 33W          | 166lm/W           | 3000K             | >80 |
| 55.01606.81.E.65.LNS. Δ | 65°    | 5500lm             | 33W          | 166lm/W           | 3500K             | >80 |
| 55.01606.84.E.65.LNS. Δ | 65°    | 5500lm             | 33W          | 166lm/W           | 4000K             | >80 |

Litetime reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.