



**PRODUCT MATERIAL**

Die-cast aluminium

**LIGHT SOURCE**

Bridgelux V10B or DtW

**MODULE LIFETIME**

Approx. 50.000 hours

**DRIVER**

Including phase cut dimmable driver

**COLORS (Δ)**

○ 3 = RAL 9003 white

● 5 = RAL 9005 black

**BEAM ANGLE**

24°

**ADJUSTABLE**

No

**DIMMABLE**

Yes

**SIZE**

Ø72 X 110mm

**OPTIONS**

<b>OPTIONAL BEAM ANGLE</b>	15°	Art. no.: 3067.010.15.0
	36°	Art. no.: 3067.010.36.0
	45°	Art. no.: 3067.010.45.0
<b>ANTI-GLARE RING</b>	<b>Black</b>	Included
	<b>Gold</b>	Art. no.: 3067.030.00.9
<b>HONEYCOMB</b>	Art. no.: 3067.040.00.0	
<b>DRIVER OPTIONS</b>	<b>1/10V</b>	250mA 1-11W Art. no.: 0111.250.30.0 This driver can only be placed externally
	<b>DALI</b>	250mA 6-13W Art. no.: 0114.250.40.1 This driver can only be placed externally

**INFORMATION**

⚠ Full warranty only applies when fixture is purchased in combination with recommended driver.



**ANTI-GLARE RING**




Black

Gold

**HONEYCOMB**



Honeycomb



Technical drawing

ARTICLE NUMBER	LAMP TYPE	BRAND	LUMINOUS FLUX	OUTPUT POWER	MODULE EFFICIENCY	COLOR TEMPERATURE	CRI	TC LIFETIME	mA
Δ See colors									
5200.270.24.Δ	V10B	Bridgelux	700lm	10W	70lm/W	2700K	>90	50.000 Hrs	250mA
5200.300.24.Δ	V10B	Bridgelux	750lm	10W	75lm/W	3000K	>90	50.000 Hrs	250mA
5200.125.24.Δ	DtW	Bridgelux	750lm	10W	75lm/W	1800-3000K	DTW >90	50.000 Hrs	250mA

Litetime reserves the right to modify or change technical, construction or LED specifications due to continuous improvements of our products and light sources.