



TRACK LIGHTING

AVAILABLE IN




Standard	Reflector					Led module		Mounting	
Dimmable	Reflector	Reflector	Reflector	Reflector	Reflector	Standard	DTW	1-phase	3-phase
Dim options		Fixture options							
Dimmable	Casambi	Honeycomb							

Lumen output	400lm
CRI	>90Ra
CCT	2700K • 3000K

FIXTURE SPECIFICATIONS

3-Circuit

1-Circuit



Fixture weight: 200 grams



Housing material	Die cast aluminium
Material finish	Powder coating (anodised for Premium finish)
RAL colour	9005 (Black) • 9016 (White) • 1036 (Gold)
Fixture type	3-circuit track light
LED Module	Bridgelux V6 LED
Driver	Triac dimmable driver
Adapter	Powergear 3-circuit track adapter
Number of light sources	1
Adjustability	350° rotatable and 90° tiltable
IP rating	IP20
Expected lifetime	L90 / B10 @ 70.000 hours
Photobiological safety	RG1 Unlimited
Power factor	> 0.9
Colour consistency	3 SDCM
Warranty	3 years on LED module and driver

FIXTURE VARIATIONS

LED module	Lumen	Light colour	Efficiency (Lm/W)	Power	Dim options
Bridgelux V6 LED	400lm	927	80	6.0W	Triac / DALI / Casambi
Bridgelux V6 LED	400lm	930	83	6.0W	Triac / DALI / Casambi
Bridgelux V6 LED	400lm	Dim to Warm 1800K - 3000K	83	6.0W	Triac / DALI / Casambi

Fixture variations:

- ¹⁾ Lumen output of LED module (COB) is displayed as net lumen and is subject to 10% tolerance of real time light output (set by international standards)
- ²⁾ Colour temperature notation is composed of CRI value, indicated by the first digit, and CCT in Kelvin, indicated by the following 2 digits. Accuracy of the Correlated Colour Temperature (CCT) is subject to a tolerance of up to +/- 150 Kelvin compared to nominal value.
- ³⁾ Fixture efficiency is displayed in lumens per watt and is calculated based on the gross lumen output and power consumption of both the LED module and driver
- ⁴⁾ Mentioned wattage applies for the total power consumption of the fixture, including both LED module and driver.

Technical data can be changed by Internova Professional Lighting without prior notice.

ARTICLE CODE CONFIGURATOR

IN

Clear filters

MOUNTING

☐ 3-phase

☐ 1-phase

LIGHT COLOUR

☐ 2700K

☐ 3000K

☐ Dim to Warm

REFLECTOR

☐ 15°

☐ 40°

☐ 24°

☐ 55°

FIXTURE COLOUR

☐ Black

☐ Black / Gold

☐ Black / White

☐ White

☐ White / Gold

☐ White / Black

☐ Champagne gold

DIM OPTIONS

☐ DALI dim

☐ Casambi

STANDARD

☒ Triac dim

FIXTURE OPTIONS

☐ No option

☐ Honeycomb

LUMEN OUTPUT

☐ 400lm

Article code configurator:

- ¹⁾ This configurator may not be compatible with all PDF readers. For an optimal experience, please open this document using Google Chrome

POLAR DIAGRAMS

